

<<第十二届世界钛会论文集（卷3）>>

图书基本信息

书名：<<第十二届世界钛会论文集（卷3）>>

13位ISBN编号：9787030338945

10位ISBN编号：7030338944

出版时间：2012-1

出版时间：科学出版社

作者：本社 编著

页数：573

版权说明：本站所提供下载的PDF图书仅提供预览和简介，请支持正版图书。

更多资源请访问：<http://www.tushu007.com>

内容概要

第十二届钛会是系列会议的第十二届，钛会自1968年开始，每四年举办一次，旨在召集世界钛界同仁，共商钛科技发展大计。

钛会覆盖了钛的各个方面，包括从矿石到成品的完整的生产路线，新合金和加工的发展，微观结构和性能的评价以及所有领域钛的应用。

世界七大钛国，包括美国、俄罗斯、日本、英国、法国、中国和德国组成的国际组织委员会保证了钛研究、发展和应用的各个新的、感兴趣领域都将被讨论。

书籍目录

7. Near Net Shape Processing

Net Shape Processing of Titanium Alloys for Enhanced Performance and Improved Affordability

Synthesis of Amorphous/Nanocrystalline Ni-Ti Biomaterial Powders by Mechanical Alloying

Single Press and Sinter of ITP Process Ti6Al4V Powder

Layer Build of Titanium Alloy Complex-Geometry Components for Rocket Engines

Optimization of Parameters for Pressureless Sintering of Titanium and Ti-6Al-4V Powders by a Taguchi Method

Beta Processing of Ti6Al4V-Microstructure and Properties

Simulating and Predicting the Process of Hot isostatic Pressing of a Casing Part with Ti6Al4V Powder

Microstructure and Mechanical Properties of Laser Metal Deposited Ti-6Al-4V

Insights into the Formation of Titanium in the TiROT M Process

Microstructural Manipulation and Mechanical Properties of Ti-24Nb-4Zr-8Sn alloy Manufactured by Selective

8. Environmental Behavior

Development of Titanium Alloys with Corrosion Resistance in Aqueous Fluoride Solutions

The Effect of High Temperature Oxidation on the Fatigue Fracture Mechanism of Ti-4Al-2V Alloy

Notched Tensile Fracture of Ti-6Al-4V Laser Welds at Elevated Temperatures

Suppressing the Alpha-casing of Ti-alloys by a Combined Al-and F-treatment

Solid Metal Induced Embrittlement of Titanium Alloys in Contact with Copper

High Cycle Fatigue Properties of Ti-834 Following Prolonged Thermal Exposure in air

The Research on the Mechanism and Prevention of Solid Particle Erosion for Titanium Alloy

Corrosion Resistance and Hardness Properties of Electroless Ni-P Coatings on Ti-6Al-4V Titanium Alloy

Influence of Hydrogen Environment on the Mechanical Properties of Cast and-Electron Beam Melted Ti-6Al-4V

Study on the Microstructure and Properties of Ti40 Titanium Alloy by Thermo-hydrogenation Treatment

Characterization of TiNi Gas-atomized Powders and Thermally Sprayed Coating

In Situ Formation of TiN Coating on TA2 Pure Titanium via Laser Surface Nitriding

The Influence of Pre-oxidation in a Silica-powder Pack on the

- Cyclic Oxidation Behavior of High Nb-TiAl
Titanium and rFitanium Alloy Coatings for Corrosion
Protection
Inoxidizability of NiCoCrAlY Coatings Deposited on Ti Alloys by
Magnetron Sputtering
Properties of Lanthanum Containing Free-machining Titanium Alloys
with Regard to Localized Corrosion
A Mechanism of Nickel Deposition on Titanium Substrate by High
Speed Electroplating
Anodization Replica of Precipitates in Age-Hardening Ti
Alloys
Study of Surface Properties of Ti-6Al-4V with Double-glow Plasma
Non-hydrogen Carburizing
9. Aerospace Applications
Extending the Use of Titanium Alloys on A350XWB
Microstructure and Properties of the AlCuFeCr Coating Magnetron
Sputtered on TIMETAL 834
Producing Titanium Alloys with Sub Microcrystalline Structure for
Manufacturing Parts of Turbine Engine
A Novel Approach For The Fabrication of High Performance Titanium
Alloy Laminate For Aerospace Application
-
10. Biomedical and Healthcare Applications
11. Emerging Applications and Market
12. Marine Applications
Author index

章节摘录

It should be noted that the proposed model has been successfully applied to quantitatively exhibit the dynamic evolution of a phase in TC17 titanium alloy with lamellar microstructure. Hence, the realization of quantification characterization about the evolution of lamellar phase takes place of the traditional method that whether the globularization phenomenon occurred. In the present investigation, with the help of the basic theory of stereology and quantitative metallography and analysis platform of quantification image software, a rigorous and available model of quantification of microstructural features was developed. Previously, the phase volume fraction was measured using area method, and the mean intercept method was employed to measure the grain and colony size. Based on the conventional methods mentioned above, a novel approach that measuring the mean thickness of lamellae in colony using Boolean operation is proposed in this work, which is shown in Figure 1. The feature parameters of microstructures in titanium alloys extracted using this method include phase volume fraction, grain size, thickness of Widmanstätten lamellae, colony scale size, thickness and orientation of a phase. It not only reduces the error which is associated with the lineation by users but also enhances the reliability of measured data. Moreover, in order to unify the measurement standard of a phase in the basket weave, mixed and equiaxed microstructures of typical titanium alloys and take the continuity and simplicity of quantification into consideration, the evaluated parameter of Feret Ratio was referred to present the evolution of colony, phase and modeling the correlation of process, microstructure and mechanical property of titanium alloys. The orientation of a phase was presented by the angle to the primary axis of a phase and its vertical direction, which suggests that the characterization model of evolution and orientation behavior in a phase during hot deformation of titanium alloys has been established, as shown in Figure 2.

编辑推荐

《第十二届世界钛会论文集（卷3）》是写7个平行会议，通过会议在以下十二个主题展开：冶炼，锻造加工，微观组织演变，性能，金属间化合物及金属基复合材料，构件制造，近净形加工，环境行为，航空航天应用，生物—医疗保健应用，新兴的应用和市场，海洋应用。

版权说明

本站所提供下载的PDF图书仅提供预览和简介，请支持正版图书。

更多资源请访问:<http://www.tushu007.com>